



## SDS Information

---

### Section 1. CHEMICAL PRODUCT SECTION

Product Name: R-410a Refrigerant  
Date Prepared: 05-2015

Manufacturer: Weitron, Inc.  
801 Pencader Dr.  
Newark, DE 19702  
PH: (800)-398-3816  
Fax: (302)-455-6656

---

### Section 2. HAZARDS IDENTIFICATION

PRODUCT HAZARD CATEGORY: Gases under pressure. Liquefied Gas.  
LABEL CONTENT: Pictogram



SIGNAL WORD: **WARNING**

HAZARDOUS WARNINGS: Contains gas under pressure; may explode if heated.

HAZARDOUS PREVENTION MEASURES: Protect from sunlight. Store in a well-ventilated place.

OTHER HAZARDS: Misuse or intentional inhalation abuse may lead to death without warning.

Vapor is heavier than air and can cause suffocation by reducing oxygen available for breathing. Rapid evaporation of the liquid may cause frostbite.

---

### Section 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	CHEMICAL FAMILY Description	Weight %
354-33-6	Pentafluoroethane (HFC-125)	50%
75-10-5	Difluoromethane (HFC-32)	50%

This product contains no known hazardous materials as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Emergency Overview:

Contents under pressure. "Frostbite-like" effects may occur if the liquid or escaping vapors contact the eyes or skin. Inhalation overexposure may cause: Central nervous system depression with dizziness, confusion, loss of coordination, drowsiness, unconsciousness or death. Suffocation if air is displaced by vapors.

Potential Health Effects:

Eyes: Frostbite-like" effects may occur if the liquid or escaping vapors contact the eyes.

Skin: Frostbite-like" effects may occur if the liquid or escaping vapors contact the skin.

Inhalation: Inhalation overexposure may cause: Central nervous system depression with dizziness, confusion, loss of coordination, drowsiness, unconsciousness or death. Suffocation, if air is displaced by vapors.

Ingestion: Not considered a potential route of exposure

Carcinogenicity: No known cancer hazards.

HMIS Classification:

Health	1
Flammability	0
Reactivity	1

---

**Section 4.**

**FIRST AID MEASURES**

Eye Contact:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

Skin Contact:

Wash affected area immediately with large amounts of soap or water for 15 minutes. Remove contaminated clothing and shoes, and wash before reusing. Treat affected area for frostbite if necessary by gently warming. May irritate skin. If irritation continues contact Physician.

Inhalation:

If inhaled, immediately remove to area with fresh air. If not breathing give artificial respiration. If breathing is difficult give oxygen. Contact Physician..

Ingestion:

Is not considered a potential route of exposure.

Advice to Physician

Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with caution and only in situations of emergency life support.

---

**Section 5.**

**FIRE FIGHTING MEASURES**

Flash Point:

Does not flash

Flammable limits in Air

LEL: None  
UEL: None  
Based on ASHRAE Standard 34 with match ignition

**Extinguishing Media:**

Water, carbon dioxide, foam or dry powder.

**Fire & Explosion Hazards:**

Not flammable at ambient temperatures and atmospheric pressure. Material will become combustible when mixed with air under pressure and exposed to ignition sources. Hazardous thermal decomposition products (Carbon oxides, Hydrogen Fluoride, Carbonyl fluoride)

**Fire Fighting Instructions:**

Contents under pressure and container may rupture when exposed to high temperature. Product may act as asphyxiate. As in any fire, wear self-contained breathing apparatus pressure-demand MSHA/NIOSH (approved or equivalent) and full protective gear. Contain runoff water. Contaminated extinguishing water must be disposed of in accordance with applicable regulations. Avoid breathing smoke, fumes, and decomposition products.

---

**Section 6. ACCIDENTAL RELEASE MEASURES**

**Safeguards (Personnel)**

Evacuate personnel to safe areas. Ventilate area. Wear appropriate personal protective equipment

**Initial Containment**

Contain spilled material. Do not allow material to enter soil or surface water. Product evaporates

**Spill Procedures**

Contain spilled material. Large spillage should be dammed-off and pumped into containers.

---

**Section 7. HANDLING AND STORAGE**

**Handling (Personnel)**

Do not breathe vapors. Do not get in eyes, on skin or clothing. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Use appropriate personal protective equipment when using material. Do not puncture or drop cans. Do not expose cans to high heat or open flame.

**Handling (Physical Aspects)**

Avoid contact with strong oxidizing agents. Avoid contact with eyes and skin. Keep away from children.

**Storage Precautions**

Protect containers from physical damage. Do not Puncture, incinerate or store cans above 120°F. Keep in cool dry area out of direct sunlight.

---

**Section 8. EXPOSURE CONTROL/PERSONAL PROTECTION**

**Engineering Controls:**

Good general ventilation should be sufficient under normal use conditions.

**Eye/Face Protective Requirements:**

Wear safety glasses, splash goggles or face shield. Where contact with this material is likely, eye protection is recommended.

**Skin Protection:**

Wear protective gloves to minimize skin contamination. When prolonged or frequently repeated contact could occur, use protective clothing impervious to this material.

**Respiratory Protection:**

Under normal use conditions, with adequate ventilation, no special handling equipment is required.

**Miscellaneous**

Use good personal hygiene practices; limit exposure to product whenever possible to minimize clean-up.

**Exposure Limit Guidelines**

**Exposure Limit Values**

**Pentafluoroethane**

AEL 1,000 ppm 8 & 12 hr. TWA

**Difluoromethane**

AEL 1,000 ppm 8 & 12 hr. TWA

AEL is the Acceptable Exposure Limit as determined by Dupont

---

**Section 9.**

**PHYSICAL AND CHEMICAL PROPERTIES**

Form:	Liquefied Gas
Color:	Colorless
Odor:	Slight ethereal odor
Boiling Point:	-51.4°C (-60.5°F)
Solubility in Water:	not determined
Vapor Pressure:	200.4 psig @ 70°F
Vapor Gravity:	Not Determined
Specific Gravity:	1.06 @ 25°C (77°F)
Liquid Density:	1.032 g/cm <sup>3</sup> @25°C (77°F)
PH:	<7
Volatile Organic Compounds (VOC)	Not Determined

**Flash point & additional flammability data found in section 5.**

---

**Section 10.**

**STABILITY AND REACTIVITY**

**Stability**

This compound is stable at ambient conditions.

#### Polymerization

Hazardous polymerization will not occur.

#### Conditions to avoid

Do not mix with air above atmospheric pressure or oxygen. Do not puncture, incinerate or store cans above 120°F. Keep in cool dry area out of direct sunlight.

#### Incompatibility with other materials

Avoid contact with strong oxidizing agents. Incompatible with alkali or alkaline earth metals – powdered aluminum, Zink, etc.

#### Decomposition

Avoid high temperatures or open flames which can decompose material forming hydrofluoric acid, and possibly carbonyl halides.

---

### Section 11.

### TOXICOLOGY INFORMATION

#### Pentafluoroethane (HFC-125)

Dermal : not applicable

Oral : not applicable

Inhalation 4 h LC50 : >800000ppm, rat

Inhalation (LOAEC) : 100000ppm dog

Cardiac sensitization

Skin Irritation : No irritation, not tested on animals

Not expected to cause skin irritation based on expert review of properties of the substance

Eye Irritation : No irritation, not tested on animals

Not expected to cause skin irritation based on expert review of properties of the substance

Skin Sensitization : Not tested on animals

Not expected to cause sensitization based on expert review of the properties of the substance

Repeated dose toxicity : Inhalation

Rat

No toxicologically significant effects were found

Carcinogenicity : Overall weight of evidence indicates that the substance is not carcinogenic

Mutagenicity : Did not cause genetic damage in animals

Did not cause genetic damage in cultured mammalian cells

Did not cause genetic damage in cultured bacterial cells

Reproductive toxicity : Evidence suggests the substance is not a reproductive toxin in animals. Information given is based on data obtained from similar substances

Teratogenicity : Animal testing showed no developmental toxicity

Further information : Cardiac sensitization threshold limit: 490000 mg/m<sup>3</sup>

#### Difluoromethane (HFC-32)

Dermal : not applicable

Oral : not applicable

Inhalation 4 h LC50 : >520000ppm, rat

Inhalation LOAEC : >300000ppm, dog

Skin irritation : No skin irritation, not tested on animals.

Eye irritation	Not expected to cause skin irritation based on expert review of the properties of the substance : No eye irritation, not tested on animals
Skin sensitization	Not expected to cause eye irritation based on expert review of the properties of the substance : Not tested on animals Not expected to cause sensitization based on expert review of the properties of the substance There are no reports of human respiratory sensitization
Repeated dose toxicity	: Inhalation Rat No toxicologically significant effects were found
Carcinogenicity	: Overall weight of evidence indicates that the substance is not carcinogenic
Mutagenicity	: Did not cause genetic damage in animals Did not cause genetic damage in cultured mammalian cells Did not cause genetic damage in cultured bacterial cells
Reproductive toxicity	: Animal testing showed no reproductive toxicity Information given is based on data obtained from similar substances
Teratogenicity	: Animal testing showed no developmental toxicity
Further information	: Cardiac sensitization threshold limit: >638000 mg/m <sup>3</sup>

## Section 12.

## ECOLOGICAL INFORMATION

### Aqua Toxicity

#### Pentafluoroethane (HFC-125)

96 h LC50	: Danio rerio (zebra fish) >200mg/L Information given is based on data obtained from similar substances
96 h LC50	: Oncorhynchus mykiss (rainbow trout) 450mg/L Information given is based on data obtained from similar substances
96 h EC50	: Algae 142 mg/L Information given is based on data obtained from similar substances
48 h EC50	: Daphnia magna (water flea) >200 mg/L Information given is based on data obtained from similar substances

#### Difluoromethane (HFC-32)

96 h LC50	: Fish 1507 mg/L
72 h EC50	: Algae 142 mg/L
48 h EC50	: Daphnia 652 mg/L

## Section 13.

## DISPOSAL CONSIDERATIONS

### Waste Disposal

Can be used after re-conditioning. Recover by distillation or remove to a permitted waste disposal facility. Comply with Federal, State, and local regulations

### Environmental Hazards

Empty Pressure Vessels should be returned to the supplier

---

**Section 14.****TRANSPORTATION INFORMATION**

## US DOT Information:

Shipping Name : Liquefied gas, n.o.s. (Pentafluoroethane, Difluoromethane)  
Product Label : Liquefied gas, n.o.s. (Pentafluoroethane, Difluoromethane)  
Shipping Class : 2.2  
UN/NA # : 3163

## ICAO/IATA

Shipping Name : Liquefied gas, n.o.s. (Pentafluoroethane, Difluoromethane)  
Shipping Class : 2.2  
UN/NA# : UN3163  
Exceptions : Can qualify for limited quantity under special provisions  
Other information : Non-flammable

## IMDG

Shipping Name : Liquefied gas, n.o.s. (Pentafluoroethane, Difluoromethane)  
Shipping Class : 2.2  
UN/NA# : UN3163  
Exceptions : Can qualify for limited quantity under special provisions  
Other information : Non-flammable

## Other Transportation Information:

The Transport information may vary with the container and mode of shipment.

---

**Section 15.****REGULATORY INFORMATION****Miscellaneous Information**

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substance Control Act (TSCA)

This material or all of its components are listed (or considered as having been notified) on the European Inventory of Existing Chemical Substances (EINECS)

This material or all of its components are listed on the Canadian Domestic Substances List (DSL)

PA Right to Know Regulated Chemicals : Substances on the Pennsylvania Hazardous Substances List present at a concentration of 1% or more: Difluoromethane

NJ Right to Know Regulated Chemicals : Substances on the New Jersey Workplace Hazardous Substance List present at a concentration of 1% or more: Difluoromethane

---

**Section 16.****OTHER INFORMATION**

To the best of our knowledge, the information contained herein is accurate. **However, neither Weitron Inc. nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of**

**the information contained herein.** Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.